

Rheological Additive for Waterborne Systems

GENERAL INFORMATION

BENTONE® DS additive is a beneficiated, easily dispersible powdered hectorite clay.

PHYSICAL PROPERTIES

Composition	beneficiated hectorite clay
Color / Form	milky-white, soft powder
Apparent (bulk) density	Approx. 0.4 g/cm ³
Particle Size	min 93% thru 200 mesh

APPLICATIONS

- Architectural coatings, mid to high PVC
- Building materials, such as mortar based on cement and lime
- Gypsum plasters
- Lime-cement rendering
- Waterborne adhesives

KEY PROPERTIES

BENTONE® DS rheological additive

Application performance

- improves flow properties and surface quality
- improves slump/sag resistance
- reduces stickiness, provides easier troweling
- improves workability/application of plasters, promotes fast water release
- optimizes water stability of the finally cured system
- Partial replacement for cellulose ether

System stability

- prevents hard settlement of pigments/fillers
- reduces syneresis
- minimises floating/flooding of pigments

Easy to use

- can be incorporated as a powder

INCORPORATION

BENTONE® DS additive is easy to process. No increased temperature is required.

1. Add BENTONE® DS dry to a vessel containing only water.
2. Mix at highest practicable speed for 10 minutes.
3. After sufficient hydration time, introduce glycols, defoamers, biocides, dispersants etc. (mix)
4. Add pigments, fillers, and active ingredients and disperse.
5. Complete dilution.

BENTONE® DS additive provides stable gels within the pH range of 6-11.

LEVELS OF USE

Typical addition levels are 0.2 - 2.0% BENTONE® DS additive by weight of total formulation, depending upon the degree of suspension, the rheological properties or viscosity required.

HEALTH AND SAFETY DATA

Before using this product please consult our Material Safety Data Sheet (MSDS) for information on safe handling and storage. MSDS can be found on the company website at www.elementis-specialties.com.

STORAGE RECOMMENDATIONS

Store in a dry place. BENTONE® DS additive will absorb moisture in high humidity conditions.

SHELF LIFE

BENTONE® DS has a shelf life of 4 (four) years from date of manufacture.

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

QUALITY ASSURANCE

Since 1992 the company is a holder of the ISO 9001 / ISO 9002 certificates, which guarantees that all operations are conducted according to the stipulated standards.

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

® Trademark of Elementis Specialties, Inc.

www.elementis-specialties.com

doc April 2015

USA Head Office

Elementis Specialties, Inc.
469 Old Trenton Road
East Windsor, NJ 08512, USA
Tel.: +1 609 443 2500
Fax: +1 609 443 2422

Europe

Elementis UK Ltd.
c/o Elementis GmbH
Stolberger Strasse 370
50933 Cologne, Germany
Tel.: +49 221 2923 2066
Fax: +49 221 2923 2011

China

Deuchem (Shanghai) Chemical Co., Ltd.
99, Liayang Road
Songjiang Industrial Zone
Shanghai, China 201613
Tel.: +86 21 5774 0348
Fax: +86 21 5774 3563