

TECHNICAL DATA SHEET

BENTONE® LUXE WO

Non-animal origin rheological additive for cosmetics and toiletries

GENERAL INFORMATION

BENTONE® LUXE WO provides emulsification and rheological properties for silicone free water in oil systems.

BENTONE® LUXE WO creates extremely stable emulsions with a very light texture. Emulsions containing **BENTONE® LUXE WO** apply easily without leaving a greasy film on the skin. This light texture allows for high oil concentrations that can be used for dry, damaged skin, yet feels light and silky for even oily skin types. This unique ability to deliver high loads of oil with a dry elegant skin feel make **BENTONE® LUXE WO** ideal for all skin types.

BENTONE® LUXE WO can be used in colour cosmetics or sunscreens to disperse and suspend pigments and actives.

INCI NAME

Polyglyceryl-6 Polyricinoleate, Polyglyceryl-3 Diisostearate, Disteardimonium Hectorite

CHEMICAL & PHYSICAL PROPERTIES

Colour/Form	Tan
Viscosity, Brookfield Helipath, TF spindle, Pa.s @ 2.5 rpm	200 – 1000
Infrared	To match standard
Microbial Content	Max. 100 cfu/g

These are typical properties not to be used for specification purposes.

APPLICATIONS

- Lip care
- Eye makeup
- Lip products
- Facil makeup
- Emulsions
- Creams and lotions
- Water in silicone emulsions
- Sun protection products
- After sun products

KEY PROPERTIES

- Non-animal origin
- Rheological control
- Predictable, reproducible and stable viscosity control
- Shear-thinning viscosity
- Excellent suspension of pigments and actives
- Controlled alignment of special-effect pigments
- Thermostable viscosity raises apparent melting point and ensures cost-efficient use of UV filters
- Emulsion stabilization [w/o]
- Optimally dispersed organoclay and emulsifier
- Incorporates with medium-shear mixing
- Gives a high degree of formulating flexibility
- Provides highly reproducible results for multi-site production requirements
- Non-abrasive
- Provides smooth feel to skin
- Toxicologically safe ingredients

BENTONE® LUXE WO

SHELF LIFE

BENTONE® LUXE WO has a minimum shelf life of 2 (two) years from date of manufacture.

STORAGE RECOMMENDATIONS

Store away from excessive heat. A small amount of solvent may separate from the gel during shipment and storage. This is normal and can be mixed into the system before use.

QUALITY ASSURANCE

Quality and continuous improvement are paramount to our business. Facility manufacturing **BENTONE® LUXE WO** has established strong integrated management system and holds ISO 9001, ISO 14001, ISO 45001 and EFCI GMP certifications.

LEVEL OF USE

The level of use of the **BENTONE® LUXE WO** will depend on the formulation. Typical use levels range from 3 – 10%.

HEALTH & SAFETY

Before using this product, please consult our Safety Data Sheet (SDS) for information on safe handling and storage. The SDS can be found on the company website.

INCORPORATION

BENTONE® LUXE WO is a high viscosity, shear-thinning product. To ensure good homogeneous mixing is achieved, care must be taken to overcome the large viscosity differential existing between the **BENTONE® LUXE WO** and the other lower viscosity components.

BENTONE® LUXE WO should be added to the oil phase of the system under homogenization to ensure proper dispersion. Mix until homogeneous before adding the other ingredients.

COMPATIBILITY

BENTONE® LUXE WO was developed for non-silicone, water in oil systems.

SUSTAINABILITY

BENTONE® LUXE WO is a raw material approved under the RSPO Mass Balance system.



RSPO - 1106301

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2025, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

® Registered trademark of Elementis Specialties, Inc.

North America:

Elementis Specialties, Inc. - 469 Old Trenton Road, East Windsor, NJ 08512, USA

Europe:

Elementis Plc - The Bindery 5th Floor, 51—53 Hatton Garden, London EC1N 8HN, UK

Asia:

Deuchem (Shanghai) Chemical Co., Ltd. - 99, Lianyang Road, Songjiang Industrial Zone, Shanghai, China 201613

T: +1 609 443 2500

T: +44 207 067 2999

T: +86 21 5774 0348