

DAPRO[®] PD 801 W

A powdered defoamer for drywall joint compounds and other cement mixes where dry defoamers are required.

CHEMICAL & PHYSICAL PROPERTIES

Composition	a blend of liquid defoamer on an inert carrier.
Colour / Form	off-white to grey powder
Bulk density	22 lbs/ft ³ / 0.352 g/cm ³

These are typical properties not to be used for specification purposes.

APPLICATIONS

- **DAPRO PD 801 W** is suitable for drywall joint compounds and other cement mixes where dry defoamers are required.

LEVELS OF USE

Typically 0.3 - 1.0% on total weight, but should be optimized by testing.

HEALTH AND SAFETY

Before using this product please consult our Safety Data Sheet (SDS) for information on safe handling and storage. The SDS can be found on the company website.

STORAGE RECOMMENDATIONS

Product must be kept dry at all times. Under adequate storage conditions, can be stored for at least 24 months in a closed container. Detailed information on handling and safety can be found in the material safety data sheet. Handle in accordance with good industrial hygiene and safety practices.

SHELF LIFE

DAPRO PD 801 W has a shelf life of 2 (two) years from date of manufacture.

QUALITY ASSURANCE

Since 1992 the company is a holder of the ISO 9001 / ISO 9002 certificates, which guarantees that all operations are conducted according to the stipulated standards.

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2018, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

Trademark of Elementis Specialties, Inc.

V01 Aug. 2018

North America

Elementis
469 Old Trenton Road
East Windsor
NJ 08512, USA
Tel.: +1 609 443 2500
Fax: +1 609 443 2422

Europe

Elementis UK Ltd.
c/o Elementis GmbH
Stolberger Strasse 370
50933 Cologne, Germany
Tel.: +49 221 2923 2066
Fax: +49 221 2923 2011

Asia

Deuchem (Shanghai) Chemical Co., Ltd.
99, Lianyang Road
Songjiang Industrial Zone
Shanghai, China 201613
Tel.: +86 21 5774 0348
Fax: +86 21 5774 3563