

DAPRO® W-77

Surface Tension Modifier for Aqueous Coatings and Inks

GENERAL INFORMATION

DAPRO W-77 Interfacial Tension Modifier acts as an intermediate between areas of high and low surface tension, either within a coating or between the coating and the substrate. It will eliminate or diminish film defects such as crawling, fish eyes, and some forms of cratering. **DAPRO W-77** can also promote spreading and uniform film formation on hard-to-wet or contaminated surfaces. **DAPRO W-77** also provides excellent recoatability. **DAPRO W-77** is free of alkylphenolethoxylates and silicone.

CHEMICAL & PHYSICAL PROPERTIES

Appearance	Clear liquid
Solids	50%
Flash Point	122°F / 50°C
Specific Gravity	1.03
Brookfield Viscosity cps	18-38 (25°C)
Surface Tension in water at 0.05% (dynes/cm)	33

These are typical properties not to be used for specification purposes.

APPLICATIONS

- Waterborne Paint & Coatings
- Industrial Coatings
- Maintenance finishes
- Inks
- Adhesives

KEY PROPERTIES

- Does not cause intercoat adhesion problems
- Improves substrate wetting
- Reduces defects caused by low surface tension additives
- Promotes improved flow and leveling

INCORPORATION

DAPRO W-77 is a low viscosity fluid that can be easily incorporated into the formulation as supplied.

DAPRO W-77 is suitable for addition at any stage of manufacture into pigmented or clear coatings.

LEVELS OF USE

Addition of 0.25 – 1.00% of **DAPRO W-77** on total formulation will provide optimum performance.

HEALTH AND SAFETY

Before using this product please consult our Safety Data Sheet (SDS) for information on safe handling and storage. The SDS can be found on the company website.

STORAGE RECOMMENDATIONS

DAPRO W-77 should be at temperatures between 40°F/5°C and 130°F/50°C.

SHELF LIFE

DAPRO W-77 has a shelf life of four (4) years from the data of manufacture

QUALITY ASSURANCE

Quality system at the site manufacturing this product complies with and is certified to ISO 9001 quality standards.

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2025, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

© Trademark of Elementis Specialties, Inc.

V02 Dec. 2025

North America

Elementis
469 Old Trenton Road
East Windsor
NJ 08512, USA
Tel.: +1 609 443 2500

Europe

Elementis Portugal Lda.,
Rua Santos Pousada, no.262,
4000-478, Porto
Portugal
Tel: +351 221 215 791

Asia

Deuchem (Shanghai) Chemical Co., Ltd.
99, Lianyang Road
Songjiang Industrial Zone
Shanghai, China 201613
Tel.: +86 21 5774 0348