

DAPRO® DF 31

A VOC-free, water dispersible defoamer with excellent application properties

CHEMICAL & PHYSICAL PROPERTIES

Composition	a blend of hydrophobic silica, emulsifiers and mineral oil
Colour / Form	opaque off-white liquid
Flash Point	165°C / 330°F
Specific gravity	0.90
Viscosity, Brookfield	450 cps / 450 mPas

These are typical properties not to be used for specification purposes.

APPLICATIONS

- **DAPRO DF 31** is effective in high quality waterborne inks, adhesives and industrial coatings and is particularly useful for low sheen paints and coatings.

KEY PROPERTIES

- **DAPRO DF 31** provides excellent foam suppression and defoaming performance.
- **DAPRO DF 31** is readily dispersible in water.

INCORPORATION

DAPRO DF 31 shows excellent compatibility and is suitable for use in the let down stage of sensitive coatings systems where optical properties are very important (e.g. gloss, transparency). A ladder study should be carried out to optimize the loading level.

LEVELS OF USE

Typically 0.1 - 1.0% on total weight, but should be optimized by testing.

HEALTH AND SAFETY

Before using this product please consult our Safety Data Sheet (SDS) for information on safe handling and storage. The SDS can be found on the company website.

STORAGE RECOMMENDATIONS

Must be mixed prior to use

Under adequate storage conditions, can be stored for at least 24 months in a closed container. Store between 50 - 100°F (10 - 38°C). If frozen thaw at room temperature and mix well. Detailed information on handling and safety can be found in the material safety data sheet. Handle in accordance with good industrial hygiene and safety practices.

SHELF LIFE

DAPRO DF 31 has a shelf life of 2 (two) years from date of manufacture.

QUALITY ASSURANCE

Since 1992 the company is a holder of the ISO 9001 / ISO 9002 certificates, which guarantees that all operations are conducted according to the stipulated standards.

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2018, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

Trademark of Elementis Specialties, Inc.

V01 Aug. 2018

North America

Elementis
469 Old Trenton Road
East Windsor
NJ 08512, USA
Tel.: +1 609 443 2500
Fax: +1 609 443 2422

Europe

Elementis UK Ltd.
c/o Elementis GmbH
Stolberger Strasse 370
50933 Cologne, Germany
Tel.: +49 221 2923 2066
Fax: +49 221 2923 2011

Asia

Deuchem (Shanghai) Chemical Co., Ltd.
99, Lianyang Road
Songjiang Industrial Zone
Shanghai, China 201613
Tel.: +86 21 5774 0348
Fax: +86 21 5774 3563