

NUOSPERSE® W-28

Dispersing Agent for Waterborne Paints, Coatings and Inks

GENERAL INFORMATION

NUOSPERSE W-28 is highly effective in wetting and dispersing pigments in aqueous systems, and stabilizing the finished dispersion to prevent flocculation and viscosity drift

CHEMICAL & PHYSICAL PROPERTIES

Appearance	Clear/ liquid
Color (Gardner)	6
pH, 1% solution in water (ASTM D 1172)	10.5
Weight per Gallon	8.7
Specific Gravity	1.05
Viscosity (cps) (ASTM D 2196)	200 - 450

These are typical properties not to be used for specification purposes.

APPLICATIONS

- Waterborne coatings & inks
- Pigment dispersions & color concentrates
- Ideal for TiO₂, organic yellows, reds, oranges, carbon blacks and extender pigments

PROPERTIES

- Rapid pigment wetting
- Works for both organic & inorganic pigments
- Increased mill output
- Maximum color development
- Long-term viscosity stability
- Non-foaming
- Compatibility in a broad range of coatings

INCORPORATION

Add prior to the pigment addition and subsequent dispersion.

LEVELS OF USE

Use 2 % by weight in the mill base to improve dispersion characteristics of the coating vehicle.

Use 5 - 15 % by weight of total formula in the manufacture of concentrated tinting colorants

HEALTH AND SAFETY

Before using this product please consult our Safety Data Sheet (SDS) for information on safe handling and storage. The SDS can be found on the company website.

STORAGE RECOMMENDATIONS

Avoid excessive heat, open flame. Protect from frost.

SHELF LIFE

NUOSPERSE W-28 has a shelf life of 4 (four) years from date of manufacture.

QUALITY ASSURANCE

Since 1992 the company is a holder of the ISO 9001 / ISO 9002 certificates, which guarantees that all operations are conducted according to the stipulated standards.

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2018, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

© Trademark of Elementis Specialties, Inc.

V01 Jul 2018

North America

Elementis Specialties, Inc.
469 Old Trenton Road
East Windsor
NJ 08512, USA
Tel.: +1 609 443 2500
Fax: +1 609 443 2422

Europe

Elementis UK Ltd.
c/o Elementis GmbH
Stolberger Strasse 370
50933 Cologne, Germany
Tel.: +49 221 2923 2066
Fax: +49 221 2923 2011

Asia

Deuchem (Shanghai) Chemical Co., Ltd.
99, Lianyang Road
Songjiang Industrial Zone
Shanghai, China 201613
Tel.: +86 21 5774 0348
Fax: +86 21 5774 3563